

APPENDIX TO AERODROME GROUND MOVEMENT CHART - ICAO

TAXIWAYS

DESIGNATOR (1)	WIDTH (M)	BEARING STRENGTH	SURFACE TYPE	EDGE LIGHTS	EDGE LIGHTS ON THE CURVES ONLY	CENTRE LINE LIGHTS	REMARKS
1	2	3	4	5	6	7	8
A1	19	PCR 790/F/B/X/T PCN 80/F/A/W/T	ASPH	•	-	-	(2)
A3	23	PCR 720/F/A/X/T PCN 106/F/A/W/T	ASPH	•	-	-	(3)
A5	30	PCR 790/F/B/X/T PCN 66/F/A/W/U	ASPH	•	-	-	
A6	26	PCR 720/F/A/X/T PCN 120/F/A/W/T	ASPH	•	-	•	
A7	30	PCR 720/F/A/X/T PCN 120/F/A/W/T	ASPH	•	-	•	
B1	25	PCR 720/F/A/X/T PCN 120/F/A/W/T	ASPH	-	-	•	
B3	30	PCR 720/F/A/X/T PCN 66/F/A/W/U	ASPH	•	-	•	
B5	29	PCR 720/F/A/X/T PCN 66/F/A/W/U	ASPH	-	•	•	
B6	29	PCR 720/F/A/X/T PCN 92/F/A/W/T	ASPH	-	•	•	
B7	24	PCR 720/F/A/X/T PCN 93/F/A/W/T	ASPH	-	•	•	
B8	30	PCR 720/F/A/X/T PCN 120/F/A/W/T	ASPH	-	•	•	
B9	23	PCR 720/F/A/X/T PCN 83/F/A/W/T	ASPH	-	•	•	
B10	31	PCR 720/F/A/X/T PCN 120/F/A/W/T	ASPH	•	-	•	
C1	23	PCR 720/F/A/X/T PCN 61/F/C/W/T	ASPH	-	•	•	
C2	29	PCR 720/F/A/X/T PCN 120/F/A/W/T	ASPH	•	-	• (*)	(*) Unidirectional
C3	30	PCR 630/R/A/W/T PCN 120/F/A/W/T	ASPH	•	-	-	Longitudinal slope 2.5%
C4	29	PCR 720/F/A/X/T PCN 120/F/A/W/T	ASPH	•	-	•	
C5	30	PCR 720/F/A/X/T PCN 120/F/A/W/T	ASPH	•	-	•	Longitudinal slope 2.3%
C6	30	PCR 720/F/A/X/T PCN 120/F/A/W/T	ASPH	•	-	•	Longitudinal slope 2.2%
D1	-	-	ASPH	-	-	-	TWY not AVBL
D2	30	PCR 720/F/A/X/T PCN 120/F/A/W/T	ASPH	•	-	•	
E1	29	PCR 720/F/A/X/T PCN 66/F/A/W/U	ASPH	•	-	•	Longitudinal slope 1.9%
E3	30	PCR 720/F/A/X/T PCN 66/F/A/W/U	ASPH	•	-	•	

• Led

• Halogen

- (1) For TWY suitable for A380 see chart AD 2.EBBR-GMC.06a. For TWY suitable for B747-8F see chart AD 2.EBBR-GMC.06b.
- (2) Only to be used by aircraft to and from EBMB.
- (3) Compulsory for aircraft with wingspan > 45 M to/from EBMB