

GEN 2.2 Abbreviations Used in AIS Publications

Abbreviations marked by an asterisk (*) are either different from or not contained in *ICAO Doc 8400*.

A

A	Amber
*A	Ampere
AAA	(or AAB, AAC, etc. in sequence) Amended meteorological message (message type designator)
A/A	Air-to-air
AAD	Assigned altitude deviation
AAIM	Aircraft autonomous integrity monitoring
AAL	Above aerodrome level
AAR	Air to air refuelling
ABI	Advance boundary information
ABM	Abeam
ABN	Aerodrome beacon
ABT	About
ABV	Above
AC	Alto cumulus
ACARS	Aircraft communication addressing and reporting system
ACAS	Airborne collision avoidance system
ACC	Area control centre or area control
ACCID	Notification of an aircraft accident
*A-CDM	Airport collaborative decision making
ACFT	Aircraft
*ACID	Aircraft identification
ACK	Acknowledge
ACL	Altimeter check location
*ACL	ATC clearances and instructions
*ACM	ATC Communications Management
ACN	Aircraft classification number
ACP	Acceptance (message type designator)
*ACR	Aircraft classification rating
ACPT	Accept or accepted
ACT	Active or activated or activity
*ACU	Air control unit
AD	Aerodrome
ADA	Advisory area
ADC	Aerodrome chart
*ADC	Air defence controller
ADDN	Addition or additional
*ADEP	Airport of departure
*ADES	Airport of destination
ADF	Automatic direction-finding equipment
ADIZ	Air defence identification zone
ADJ	Adjacent
*ADNC	Air Defence Notification Cell
ADO	Aerodrome office (specify service)
*ADP	Automatic data processing
ADR	Advisory route
ADS	The address [when this abbreviation is used to request a repetition, the question mark (IMI) precedes the abbreviation, e.g. IMI ADS] (to be used in AFS as a procedure signal)
ADS-B	Automatic dependent surveillance - broadcast
ADS-C	Automatic dependent surveillance - contract
ADSU	Automatic dependent surveillance unit
ADVS	Advisory service
ADZ	Advise
AES	Aircraft earth station
AFIL	Flight plan filed in the air
AFIS	Aerodrome flight information service
*AFIZ	Aerodrome flight information zone
AFM	Yes or affirm or affirmative or that is correct
AFS	Aeronautical fixed service
AFT	After . . . (time or place)
AFTN	Aeronautical fixed telecommunication network

A/G	Air-to-ground
AGA	Aerodromes, air routes and ground aids
AGL	Above ground level
AGN	Again
AIC	Aeronautical information circular
AIDC	Air traffic services interfacility data communication
*AIM	ATFM information message
AIM	Aeronautical Information Management
AIP	Aeronautical information publication
AIRAC	Aeronautical information regulation and control
AIREP	Air-report
AIRMET	Information concerning en-route weather phenomena which may affect the safety of low-level aircraft operations
*AIRPROX	Aircraft proximity
AIS	Aeronautical Information Services
ALA	Alighting area
ALERFA	Alert phase
*ALO	Air Liaison Officer
ALR	Alerting (message type designator)
ALRS	Alerting service
ALS	Approach lighting system
ALT	Altitude
ALTN	Alternate or alternating (light alternates in colour)
ALTN	Alternate (aerodrome)
AMA	Area minimum altitude
*AMC	Airspace Management Cell
*AMC	ATC microphone check
AMD	Amend or amended (used to indicate amended meteorological message; message type designator)
AMDT	Amendment (AIP amendment)
*AMHS	ATS message handling system
*AMO	Aerodrome Meteorological Office
AMS	Aeronautical mobile service
AMSL	Above mean sea level
AMSS	Aeronautical mobile satellite service
*ANA	Administration de la navigation aérienne
ANC	Aeronautical chart - 1:500000 (followed by name/title)
ANCS	Aeronautical navigation chart - small scale (followed by name/title and scale)
*ANM	ATFM notification message
ANS	Answer
AO	Aircraft Operator
AOC	Aerodrome obstacle chart (followed by type and name/title)
AP	Airport
APAPI	Abbreviated precision approach path indicator
APCH	Approach
APDC	Aircraft parking/docking chart (followed by name/title)
APN	Apron
*APOC	Airport operations centre
APP	Approach control office or approach control or approach control service
APR	April
APRX	Approximate or approximately
APSG	After passing
APU	Auxiliary power unit
APV	Approach procedure with vertical guidance
*AR	Authorization required
ARC	Area chart
*ARES	Airspace reservation
ARNG	Arrange
ARO	Air traffic services reporting office
ARP	Aerodrome reference point
ARP	Air-report (message type designator)
ARQ	Automatic error correction
ARR	Arrival (message type designator)
ARR	Arrive or arrival
ARS	Special air-report (message type designator)
ARST	Arresting [specify (part of) aircraft arresting equip-

	ment]
AS	Altostratus
ASAP	As soon as possible
ASC	Ascend to or ascending to
ASDA	Accelerate-stop distance available
ASE	Altimetry system error
ASHTAM	Special series of NOTAM notifying, by means of a specific format, change in activity of a volcano, a volcanic eruption and/or volcanic ash cloud that is of significance to aircraft operations
*A-SMGCS	Advanced surface movement guidance and control system
ASPH	Asphalt
*ASR	Aerodrome surveillance radar
AT	At (followed by time at which weather change is forecast to occur)
ATA	Actual time of arrival
ATC	Air traffic control (in general)
*ATCC	Air traffic control centre (military abbreviation)
ATCSMAC	Air traffic control surveillance minimum altitude chart (followed by name/title)
ATD	Actual time of departure
*ATFCM	Air traffic flow and capacity management
ATFM	Air traffic flow management
ATIS	Automatic terminal information service
ATM	Air traffic management
ATN	Aeronautical telecommunication network
ATP	At . . . (time or place)
ATS	Air traffic services
ATTN	Attention
AT-VASIS	Abbreviated T visual approach slope indicator system
ATZ	Aerodrome traffic zone
AUG	August
*AUP	Airspace Use Plan
AUTH	Authorized or authorization
AUTO	Automatic
AUW	All up weight
AUX	Auxiliary
AVBL	Available or availability
AVG	Average
AVGAS	Aviation gasoline
AWOS	Automatic Weather Observation System
AWTA	Advise at what time able
AWY	Airway
AZM	Azimuth

B

B	Blue
BA	Braking action
BARO-VNAV	Barometric vertical navigation
BASE	Cloud base
BCFG	Fog patches
BCN	Beacon (aeronautical ground light)
BCST	Broadcast
BDRY	Boundary
BECMG	Becoming
BFR	Before
BKN	Broken
BL	Blowing (followed by DU = dust, SA = sand or SN = snow)
BLDG	Building
BLO	Below clouds
BLW	Below . . .
BOMB	Bombing
BR	Mist
BRF	Short (used to indicate the type of approach desired or required)
BRG	Bearing
BRKG	Braking
BS	Commercial broadcasting station
BTL	Between layers
BTN	Between

BUFR	Binary universal form for the representation of meteorological data
*BVLOS	Beyond visual line of sight

C

C	Centre (runway identification)
C	Degrees Celsius (centigrade)
CA	Course to an altitude
CAA	Civil Aviation Authority or Civil Aviation Administration
*CANAC	Computer Assisted National Air traffic control Centre
*CAS	Close Air Support
CAT	Category
CAT	Clear air turbulence
CAVOK	Visibility, cloud and present weather better than prescribed values or conditions
CB	Cumulonimbus
*CBA	Cross-border area
CC	Cirrocumulus
CCA	(or CCB, CCC, etc. in sequence) Corrected meteorological message (message type designator)
CCO	Continuous climb operations
*CCTV	Closed circuit television
CD	Candela
CDN	Co-ordination (message type designator)
CDO	Continuous descent operations
CDR	Conditional route
*CENOR	Central and Northern region (an organisation of NATO nations that developed specifications for aeronautical charts for the use of MIL crew)
*CEU	Central executive unit
CF	Change frequency to . . .
CF	Course to a fix
*CFIT	Controlled flight into terrain
CFM	Confirm or I confirm (to be used in AFS as a procedure signal)
CGL	Circling guidance light(s)
CH	Channel
CHEM	Chemical
CHG	Modification (message type designator)
CI	Cirrus
CIDIN	Common ICAO data interchange network
CIV	Civil
CK	Check
CL	Centre line
CLA	Clear type of ice formation
CLBR	Calibration
CLD	Cloud
CLG	Calling
CLIMB-OUT	Climb-out area
CLR	Clear(s) or cleared to . . . or clearance
CLRD	Runway(s) cleared
CLSD	Close or closed or closing
CM	Centimetre
CMB	Climb to or climbing to
C MPL	Completion or completed or complete
CNL	Cancel or cancelled
CNL	Flight plan cancellation (message type designator)
CNS	Communications, navigation and surveillance
COM	Communications
*COMAO	Composite Air Operations
*COMOPS AIR&SPACE	Command Operations Air and Space
CONC	Concrete
COND	Condition
CONS	Continuous
CONST	Construction or constructed
CONT	Continue(s) or continued
COOR	Coordinate or coordination
COORD	Coordinates
COP	Change-over point
COR	Correct or correction or corrected (used to indicate corrected meteorological message; message type designator)

COT	At the coast	DOM	Domestic
COV	Cover or covered or covering	DP	Dew point temperature
CPDLC	Controller-pilot data link communications	*DPM	Motorized deltaplane
CPL	Current flight plan (message type designator)	DPT	Depth
*CPSRA	Critical part of the security restricted area	DR	Dead reckoning
CRC	Cyclic redundancy check	DR	Low drifting (followed by DU = dust, SA = sand or SN = snow)
*CRC	Control and reporting centre	DRG	During
CRM	Collision risk model	DS	Duststorm
*CRNA	Centre en Route de la Navigation Aérienne	DSB	Double sideband
CRP	Compulsory reporting point	DTAM	Descend to and maintain
CRZ	Cruise	DTG	Date-time group
CS	Call sign	DTHR	Displaced runway threshold
CS	Cirrostratus	DTRT	Deteriorate or deteriorating
*CSAR	Combat search and rescue	DTW	Dual tandem wheels
CTA	Control area	DU	Dust
CTAM	Climb to and maintain	DUC	Dense upper cloud
CTC	Contact	DUPE	This is a duplicate message (signal for use in the teletypewriter service only; to be used in AFS as a procedure signal)
CTL	Control	DUR	Duration
CTN	Caution	D-VOLMET	Data link VOLMET
*CTOT	Calculated take-off time	DVOR	Doppler VOR
CTR	Control zone	DW	Dual wheels
CU	Cumulus	DZ	Drizzle
CUF	Cumuliform		
CUST	Customs		
CVR	Cockpit voice recorder		
CW	Continuous wave		
CWY	Clearway		

D

D	Downward (tendency in RVR during previous 10 minutes)
D	Danger area (followed by identification)
DA	Decision altitude
*DAT	Significant data related to data link capability
D-ATIS	Data link automatic terminal information service
*dB	Decibel
DCD	Double channel duplex
DCKG	Docking
*DCL	Data link clearance delivery service
DCP	Datum crossing point
DCPC	Direct controller-pilot communications
DCS	Double channel simplex
DCT	Direct (in relation to flight plan clearances and type of approach)
DE	From (used to precede the call sign of the calling station; to be used in AFS as a procedure signal)
DEC	December
DEG	Degrees
DEP	Depart or departure
DEP	Departure (message type designator)
DEPO	Deposition
DER	Departure end of the runway
DES	Descend to or descending to
DEST	Destination
DETRESFA	Distress phase
DEV	Deviation or deviating
DF	Direction finding
DFDR	Digital flight data recorder
*D-FIS	Data link flight information service
DFTI	Distance from touchdown indicator
*DGS	Docking guidance system
DH	Decision height
DIF	Diffuse
DIST	Distance
DIV	Divert or diverting
DLA	Delay or delayed
DLA	Delay (message type designator)
DLIC	Data link initiation capability
DLY	Daily
DME	Distance measuring equipment
DNG	Danger or dangerous
*DOC	Designated operational coverage
DOF	Date of flight

E

E	East or eastern longitude
*eAIP	Electronic aeronautical information publication
EAT	Expected approach time
*EAUP	European airspace use plan
*EAW	Early access weekend routes
EB	Eastbound
*ECAC	European Civil Aviation Conference
EDA	Elevation differential area
EDTO	Extended diversion time operations
EEE	Error (signal for use in the teletypewriter service only; to be used in AFS as a procedure signal)
EET	Estimated elapsed time
EFC	Expect further clearance
EFIS	Electronic flight instrument system
eFPL	Filed flight plan exchanged via flight and flow – information for a collaborative environment (FF-ICE) services
EGNOS	European geostationary navigation overlay service
EHF	Extremely high frequency (30 000 to 300 000 MHz)
*EHS	Enhanced surveillance
ELBA	Emergency location beacon - aircraft
ELEV	Elevation
ELR	Extra long range
*ELS	Elementary surveillance
ELT	Emergency locator transmitter
EM	Emission
EMBD	Embedded in a layer (to indicate cumulonimbus embedded in layers of other clouds)
EMERG	Emergency
*En	English
END	Stop-end (related to RVR)
ENE	East-north-east
ENG	Engine
ENR	En-route
ENRC	En-route chart (followed by name/title)
EOBT	Estimated off block time
EQPT	Equipment
EQS	Equatorial latitudes southern hemisphere
*ESA	Emergency safety altitude
ESE	East-south-east
EST	Estimate or estimated or estimate (message type designator)
*EST	Estimated (preceded by time-group)
ETA	Estimated time of arrival or estimating arrival
ETD	Estimated time of departure or estimating departure
ETO	Estimated time over significant point

*ETOT	Estimated take-off time
EUR RODEX	European regional OPMET data exchange
*EUROAT	Eurocontrol harmonised rules for operational air traffic
*EUUP	European updated airspace use plan
EV	Every
EVS	Enhanced vision system
EXC	Except
*excl	Excluded
EXER	Exercises or exercising or to exercise
EXP	Expect or expected or expecting
EXTD	Extend or extending or extended

FRNG	Firing
FRONT	Front (relating to weather)
FROST	Frost (used in aerodrome warnings)
FRQ	Frequent
FSL	Full stop landing
FSS	Flight service station
FST	First
FT	Feet (dimensional unit)
FTE	Flight technical error
FTP	Fictitious threshold point
FTT	Flight technical tolerance
FU	Smoke
FZ	Freezing
FZDZ	Freezing drizzle
FZFG	Freezing fog
FZRA	Freezing rain

F

F	Fixed
FA	Course from a fix to an altitude
*FAB	Functional airspace block
FAC	Facilities
FAF	Final approach fix
FAL	Facilitation of international air transport
*FANS	Future air navigation system
FAP	Final approach point
FAS	Final approach segment
*FASID	Facilities and Services Implementation Document
FATO	Final approach and take-off area
FAX	Facsimile transmission
FBL	Light (used to indicate the intensity of weather phenomena, interference or static reports, e.g. FBL RA = light rain)
*FBZ	Flight planning buffer zone
FC	Funnel cloud (tornado or water spout)
FCST	Forecast
FCT	Friction coefficient
FDPS	Flight data processing system
FEB	February
FEW	Few
FG	Fog
FIC	Flight information centre
FIR	Flight information region
FIS	Flight information service
FISA	Automated flight information service
FL	Flight level
FLD	Field
FLG	Flashing
*FLIP	Flight information publication
FLR	Flares
FLT	Flight
FLTCK	Flight check
FLUC	Fluctuating or fluctuation or fluctuated
FLW	Follow(s) or following
FLY	Fly or flying
FM	Course from a fix to manual termination (used in navigation database coding)
FM	From
FM	From (followed by time weather change is forecast to begin)
FMC	Flight management computer
*FMP	Flow management position
FMS	Flight management system
FMU	Flow management unit
FNA	Final approach
*FOD	Foreign object damage
FPAP	Flight path alignment point
FPL	Filed flight plan exchanged via aeronautical fixed service (AFS)
FPM	Feet per minute
FPR	Flight plan route
*FPS	Federal Public Service
FR	Fuel remaining
*Fr	French
*FRA	Free route airspace
FREQ	Frequency
FRI	Friday

G

*G	Gram
G	Green
G	Variations from the mean wind speed (gusts) (used in METAR/SPECI and TAF)
GA	General Aviation
GA	Go ahead, resume sending (to be used in AFS as a procedure signal)
G/A	Ground-to-air
G/A/G	Ground-to-air and air-to-ground
GAGAN	GPS and geostationary earth orbit augmented navigation
GAIN	Airspeed or headwind gain
GAMET	Area forecast for low-level flights
GARP	GBAS azimuth reference point
*GAT	General air traffic
GBAS	Ground-based augmentation system
GCA	Ground controlled approach system or ground controlled approach
*Ge	German
GEN	General
GEO	Geographic or true
GES	Ground earth station
GLD	Glider
GLONASS	Global orbiting navigation satellite system
GLS	GBAS landing system
GMC	Ground movement chart (followed by name/title)
GND	Ground
GNDCK	Ground check
GNSS	Global navigation satellite system
GOV	Government
GP	Glide path
GPA	Glide path angle
GPIP	Glide path intercept point
GPS	Global positioning system
GPU	Ground power unit
GPWS	Ground proximity warning system
GR	Hail
GRAS	Ground-based regional augmentation system
GRASS	Grass landing area
GRIB	Processed meteorological data in the form of grid point values expressed in binary form (aeronautical meteorological code)
GRVL	Gravel
GS	Ground speed
GS	Small hail and/or snow pellets
*GSM	Global System for Mobile Communications
GUND	Geoid undulation

H

H	High pressure area or the centre of high pressure
H...	Significant wave height (followed by figures in METAR/SPECI)
H24	Continuous day and night service

HA	Holding/racetrack to an altitude
*HAA	Height above aerodrome elevation
HAPI	Helicopter approach path indicator
*HAT	Height above touch-down
HBN	Hazard beacon
HCH	Helicopter crossing height
HDF	High frequency direction-finding station
HDG	Heading
HEL	Helicopter
*HEMS	Helicopter emergency medical service
HF	High frequency (3000 to 30000 KHZ)
HF	Holding/racetrack to a fix
*HFDL	High frequency data link
HGT	Height or height above
HJ	Sunrise to sunset
HLDG	Holding
HLP	Heliport
HLS	Helicopter landing site
HM	Holding/racetrack to a manual termination
HN	Sunset to sunrise
HNH	High latitudes northern hemisphere
HO	Service available to meet operational requirements
HOL	Holiday
HOSP	Hospital aircraft
HPA	Hectopascal
*HPMA	High performance military aircraft
HR	Hours
HRP	Heliport reference point
HS	Service available during hours of scheduled operations
HSH	High latitudes southern hemisphere
*HT	High tension
*HTA	Helicopter training area
HUD	Head-up display
HUM	Humanitarian
HURCN	Hurricane
HVDF	High and very high frequency direction-finding stations (at the same location)
HVY	Heavy
HVY	Heavy (used to indicate the intensity of weather phenomena, e.g. HVY RA = heavy rain)
HX	No specific working hours
HYR	Higher
HZ	Haze
HZ	Hertz (cycles per second)

I

IAC	Instrument approach chart (followed by name/title)
IAF	Initial approach fix
IAO	In and out of clouds
IAP	Instrument approach procedure
IAR	Intersection of air routes
IAS	Indicated airspeed
*IATA	International Air Transport Association
IBN	Identification beacon
ICAO	International Civil Aviation Organization
ICE	Icing
*ICF	Initial contact frequency
ID	Identifier or identify
IDENT	Identification
IF	Intermediate approach fix
IFF	Identification friend/foe
*IFPS	Integrated Initial Flight Plan Processing System
*IFPU	Integrated Initial Flight Plan Processing Unit
IFR	Instrument flight rules
IGA	International general aviation
ILS	Instrument landing system
IM	Inner marker
IMC	Instrument meteorological conditions
IMG	Immigration
IMI	Interrogation sign (question mark) (to be used in AFS as a procedure signal)
IMPR	Improve or improving

IMT	Immediate or immediately
INA	Initial approach
INBD	Inbound
INC	In cloud
INCORP	Incorporated
INCERFA	Uncertainty phase
*incl	Included
INFO	Information
INOP	Inoperative
INP	If not possible
INPR	In progress
INS	Inertial navigation system
INSTL	Install or installed or installation
INSTR	Instrument
INT	Intersection
INTL	International
INTRG	Interrogator
INTRP	Interrupt or interruption or interrupted
INTSF	Intensify or intensifying
INTST	Intensity
IR	Ice on runway
*IRM	Institut Royal Météorologique de Belgique
IRS	Inertial reference system
*IRU	Inertial reference unit
ISA	International standard atmosphere
ISB	Independent sideband
ISOL	Isolated

J

*JAA	Joint Aviation Authorities
JAN	January
JTST	Jet stream
JUL	July
JUN	June

K

KG	Kilograms
KHZ	Kilohertz
KIAS	Knots indicated airspeed
KM	Kilometres
KMH	Kilometres per hour
*KMI	Koninklijk Meteorologisch Instituut
KPA	Kilopascal
KT	Knots
*kVA	Kilovolt-ampere
KW	Kilowatts

L

L	Left (runway identification)
L	Litre
L	Locator (see LM, LO)
L	Low pressure area or the centre of low pressure
LAM	Logical acknowledgement (message type designator)
LAN	Inland
*LARA	Local and sub-Regional Airspace Management Support System
LAT	Latitude
*LB	Pounds
LCA	Local or locally or location or located
*LCN	Load classification number
*LCTA	Lower control area
LDA	Landing distance available
LDAH	Landing distance available, helicopter
LDG	Landing
LDI	Landing direction indicator
*LED	Light-emitting diode
LEN	Length
LF	Low frequency (30 to 300 KHZ)

*LFA	Low flying area		orological code)
LGT	Light or lighting	MET REPORT	Local routine meteorological report (in abbreviated plain language)
LGTD	Lighted		
LIH	Light intensity high	MF	Medium frequency (300 to 3000 KHZ)
LIL	Light intensity low	MHA	Minimum holding altitude
LIM	Light intensity medium	MHDF	Medium and high frequency direction-finding stations (at the same location)
LINE	Line (used in SIGMET)		
*LLFC	Low level forecast chart	MHVDF	Medium, high and very high frequency direction-finding stations (at the same location)
LM	Locator, middle		
LMT	Local mean time	MHZ	Megahertz
LNAV	Lateral navigation	MID	Mid-point (related to RVR)
LNG	Long (used to indicate the type of approach desired or required)	MIFG	Shallow fog
LO	Locator, outer	MIL	Military
LOC	Localizer	MIN	Minutes
*LOM	Compass locator at OM	*MIPS	Military instrument procedure standardization
LONG	Longitude	MIS	Missing . . . (transmission identification; to be used in AFS as a procedure signal)
LORAN	Long range air navigation system	*MJ	Megajoule
LOSS	Airspeed or headwind loss	MKR	Marker radio beacon
LPV	Localizer performance with vertical guidance	MLS	Microwave landing system
LR	The last message received by me was . . . (to be used in AFS as a procedure signal)	*MLW	Maximum landing weight
LRG	Long range	MM	Middle marker
LS	The last message sent by me was . . . or Last message was . . . (to be used in AFS as a procedure signal)	*MM	millimetre
*LSA	Light sport aircraft	MNH	Middle latitudes northern hemisphere
*LT	Left turn	MNM	Minimum
LTA	Lower control area	MNPS	Minimum navigation performance specifications
LTD	Limited	MNT	Monitor or monitoring or monitored
LTP	Landing threshold point	MNTN	Maintain
*Lu	Luxembourgish	MOA	Military operating area
LV	Light and variable (relating to wind)	MOC	Minimum obstacle clearance (required)
LVE	Leave or leaving	MOCA	Minimum obstacle clearance altitude
LVL	Level	MOD	Moderate (used to indicate the intensity of weather phenomena, interference or static reports, e.g. MOD RA = moderate rain)
*LVO	Low Visibility Operations	MON	Above mountains
LVP	Low visibility procedures	MON	Monday
*LWEP	Live weapons emergency procedure	MOPS	Minimum operational performance standards
LYR	Layer or layered	*MOPSC	Maximum operational passenger seating configuration

M

M	Metres (preceded by figures)	MOV	Move or moving or movement
M	Mach number (followed by figures)	*MPH	Statute miles per hour
M	Indicator for minimum value of runway visual range (used in the METAR/SPECI code forms)	*MPM	Metres per minute
MAA	Maximum authorized altitude	MPS	Metres per second
MAG	Magnetic	MRA	Minimum reception altitude
MAHF	Missed approach holding fix	MRG	Medium range
MAINT	Maintenance	MRP	ATS/MET reporting point
*MAN	Manual	MS	Minus
MAP	Aeronautical maps and charts	MSA	Minimum sector altitude
MAPT	Missed approach point	MSAS	Multi-functional transport satellite (MTSAT) satellite-based augmentation system
MAR	At sea	MSAW	Minimum safe altitude warning
MAR	March	*MSC	Mission Support Centre
*MARSAS	Military authority assumes responsibility for separation of aircraft	MSG	Message
MATF	Missed approach turning fix	MSH	Middle latitudes southern hemisphere
MATZ	Military aerodrome traffic zone	MSL	Mean sea level
MAX	Maximum	MSR	Message . . . (transmission identification) has been misrouted (signal for use in the teletypewriter service only; to be used in AFS as a procedure signal)
MAY	May		
MBST	Microburst	MSSR	Monopulse secondary surveillance radar
MCA	Minimum crossing altitude	MT	Mountain
MCTR	Military control zone	MTOM	Maximum take-off mass
MCW	Modulated continuous wave	*MTOW	Maximum authorized take-off weight
MDA	Minimum descent altitude	MTU	Metric units
MDF	Medium frequency direction-finding station	MTW	Mountain waves
MDH	Minimum descent height	*MVA	Minimum vectoring altitude
MEA	Minimum en-route altitude	MVDF	Medium and very high frequency direction-finding stations (at the same location)
MEDEVAC	Medical evacuation flight	MWO	Meteorological watch office
MEHT	Minimum eye height over threshold (for visual approach slope indicator systems)	MX	Mixed type of ice formation (white and clear)
MET	Meteorological or meteorology		
METAR	Aviation routine weather report (in aeronautical meteorological code)		

N

*N	Newton
N	No distinct tendency (in RVR during previous 10 min-

PRFG	Aerodrome partially covered by fog
PRI	Primary
PRKG	Parking
*PRM	Persons with reduced mobility
PROB	Probability
PROC	Procedure
PROP	Propeller
PROV	Provisional
PRP	Point-in-space reference point
PS	Plus
PSG	Passing
*PSI	Pounds per square inch
PSN	Position
PSP	Pierced steel plank
PSR	Primary surveillance radar
PSYS	Pressure system(s)
PTN	Procedure turn
PTS	Polar track structure
PWR	Power

RAI	Runway alignment indicator
RAIM	Receiver autonomous integrity monitoring
RASC	Regional AIS system centre
RASS	Remote altimeter setting source
RB	Rescue boat
RCA	Reach cruising altitude
*RCAM	Runway condition assessment matrix
RCC	Rescue co-ordination centre
RCF	Radiocommunication failure (message type designator)
RCH	Reach or reaching
RCL	Runway centre line
RCLL	Runway centre line light(s)
RCLR	Recleared
RCP	Required communication performance
*RCR	Runway condition report
RDH	Reference datum height (for ILS)
RDL	Radial
RDO	Radio
RDOACT	Radioactive
RE	Recent (used to qualify weather phenomena, e.g. RERA = recent rain)

Q

*QC	Quota count
QDL	Do you intend to ask me for a series of bearings? or I intend to ask you for a series of bearings (to be used in radiotelegraphy as a Q Code)
QDM	Magnetic heading (zero wind)
QDR	Magnetic bearing
QFE	Atmospheric pressure at aerodrome elevation (or at runway threshold)
QFU	Magnetic orientation of runway
QGE	What is my distance to your station? or Your distance to my station is (distance figures and units) (to be used in radiotelegraphy as a Q Code)
QJH	Shall I run my test tape/a test sentence? or Run your test tape/a test sentence (to be used in AFS as a Q Code)
QNH	Altimeter sub-scale setting to obtain elevation when on the ground
*QRA	Quick reaction alert
QSP	Will you relay to . . . free of charge? or I will relay to . . . free of charge (to be used in AFS as a Q Code)
QTA	Shall I cancel telegram number . . .? or Cancel telegram number . . . (to be used in AFS as a Q Code)
QTE	True bearing
QTF	Will you give me the position of my station according to the bearings taken by the D/F stations which you control? or The position of your station according to the bearings taken by the D/F stations that I control was . . . latitude . . . longitude (or other indication of position), class . . . at . . . hours (to be used in radiotelegraphy as a Q Code)
QUAD	Quadrant
QUJ	Will you indicate the TRUE track to reach you? or The TRUE track to reach me is . . . degrees at . . . hours (to be used in radiotelegraphy as a Q Code)

REC	Receive or receiver
REDL	Runway edge light(s)
REF	Reference to . . . or refer to . . .
REG	Registration
*REJ	Rejected
RENL	Runway end light(s)
REP	Report or reporting or reporting point
REQ	Request or requested
RE RTE	Re-route
RESA	Runway end safety area
*RETIL	Rapid exit taxiway indicator lighting
RF	Constant radius arc to a fix
RFFS	Rescue and fire fighting services
*RFP	Replacement flight plan (related to ATFM)
RG	Range (lights)
RHC	Right-hand circuit
RIF	Reclearance in flight
RIME	Rime (used in aerodrome warnings)
*RIS	Radar information service
RL	Report leaving
RLA	Relay to
RLCE	Request level change en route
RLLS	Runway lead-in lighting system
RLNA	Request level not available
*RMIB	Royal meteorological institute of Belgium
RMK	Remark
*RMZ	Radio mandatory zone
RNAV	Area navigation
RNG	Radio range
RNP	Required navigation performance
ROBEX	Regional OPMET bulletin exchange (scheme)
ROC	Rate of climb
ROD	Rate of descent
RON	Receiving only
*RPA	Remotely piloted aircraft
*RPAS	Remotely piloted aircraft system
RPDS	Reference path data selector
RPI	Radar position indicator
RPL	Repetitive flight plan
RPLC	Replace or replaced
RPS	Radar position symbol
RPT	Repeat / I repeat (to be used in AFS as a procedure signal)
RQ	Indication of a request (to be used in AFS as a procedure signal)
RQMNTS	Requirements
RQP	Request flight plan (message type designator)
RQS	Request supplementary flight plan (message type designator)
RR	Report reaching
RRA	(or RRB, RRC, etc. in sequence) Delayed meteorological message (message type designator)
*RSA	Restricted airspace

R

R	Right (runway identification)
R	Rate of turn
R	Red
R	Radial from VOR (followed by three figures)
R	Restricted area (followed by identification)
R	Runway (used in the METAR/SPECI code forms)
R	Received (acknowledgement of receipt; to be used in AFS as a procedure signal)
RA	Rain
RA	Resolution advisory
RAC	Rules of the air and air traffic services
*RAD	Route availability document
RAG	Ragged
RAG	Runway arresting gear

RSC	Rescue sub-centre	SIGMET	Information concerning en-route weather and other phenomena in the atmosphere that may affect the safety of aircraft operations
RSCD	Runway surface condition		
RSP	Responder beacon		
RSP	Required surveillance performance	*SIGWX	Significant weather
RSR	En-route surveillance radar	SIMUL	Simultaneous or simultaneously
RSS	Root sum square	*SITA	Société Internationale des Télécommunications Aéronautique
*RT	Right turn		
RTD	Delayed (used to indicate delayed meteorological message; message type designator)	SIWL	Single isolated wheel load
		SKED	Schedule or scheduled
RTE	Route	SLP	Speed limiting point
RTF	Radiotelephone	SLW	Slow
RTG	Radiotelegraph	SMC	Surface movement control
RTHL	Runway threshold light(s)	SMR	Surface movement radar
RTN	Return or returned or returning	SN	Snow
RTODAH	Rejected take-off distance available, helicopter	SNOCLO	Indicator for the aerodrome being closed due to snow on the runway
RTS	Return to service		
RTT	Radioteletypewriter	SNOWTAM	A special series NOTAM notifying the presence or removal of hazardous conditions due to snow, ice, slush or standing water associated with snow, slush and ice on the movement area, by means of a specific format
RTZL	Runway touchdown zone light(s)		
RUT	Standard regional route transmitting frequencies	SOC	Start of climb
RV	Rescue vessel	*SOF	Supervisor of flights
RVA	Radar vectoring area	SPECI	Aviation selected special weather report (in aeronautical meteorological code)
RVR	Runway visual range		
*RVSM	Reduced vertical separation minimum	SPECIAL	Special meteorological report (in abbreviated plain language)
RWY	Runway		
*RWYCC	Runway Condition Code		

S

S	South or southern latitude	SPI	Special position indicator
S	State of the sea (followed by figures in METAR/SPECI)	SPL	Supplementary flight plan (message type designator)
		SPOC	SAR point of contact
SA	Sand	SPOT	Spot wind
SALS	Simple approach lighting system	SQ	Squall
*SAM	Slot allocation message	SQL	Squall line
SAN	Sanitary	SR	Sunrise
SAR	Search and rescue	SRA	Surveillance radar approach
SARPS	Standards and Recommended Practices (ICAO)	SRE	Surveillance radar element of precision approach radar system
SAT	Saturday	SRG	Short range
SATCOM	Satellite communication (used only when referring generally to both voice and data satellite communication or only data satellite communication)	SRR	Search and rescue region
		SRY	Secondary
SATVOICE	Satellite voice communication	SS	Sandstorm
SB	Southbound	SS	Sunset
SBAS	Satellite-based augmentation system	SSB	Single sideband
SC	Stratocumulus	SSE	South-south-east
SCT	Scattered	SSR	Secondary surveillance radar
SD	Standard deviation	SST	Supersonic transport
SDBY	Stand by	SSW	South-south-west
SDF	Step down fix	ST	Stratus
SE	South-east	STA	Straight-in approach
SEA	Sea (used in connection with sea-surface temperature and state of the sea)	*STANAG	Standardization agreement (NATO)
		STAR	Standard instrument arrival
SEB	South-eastbound	STD	Standard
SEC	Seconds	STF	Stratiform
SECN	Section	STN	Station
SECT	Sector	STNR	Stationary
SELCAL	Selective calling system	STOL	Short take-off and landing
SEP	September	STS	Status
SER	Service or servicing or served	STWL	Stopway light(s)
SEV	Severe (used e.g. to qualify icing and turbulence reports)	SUBJ	Subject to
		SUN	Sunday
SFC	Surface	SUP	Supplement (AIP supplement)
SFO	Simulated flame out	SUPPS	Regional supplementary procedures
SG	Snow grains	SVC	Service (message type only)
SGL	Signal	SVCBL	Serviceable
SH	Showers (followed by RA = rain, SN = snow, PL = ice pellets, GR = hail, GS = small hail and/or snow pellets or combinations thereof, e.g. SHRASN = showers of rain and snow)	SW	South-west
		SWB	South-westbound
SHF	Super high frequency (3000 to 30000 MHz)	*SWC-LL	Significant weather chart - low level
SI	International system of units	SWX	Space weather
SID	Standard instrument departure	SWXC	Space weather centre
SIF	Selective identification feature	SWY	Stopway
SIG	Significant	*SYNOP	Synopsis

T

T	Temperature
T	True (preceded by a bearing to indicate reference to True North)
*T	Metric tons
TA	Traffic advisory
TA	Transition altitude
TAA	Terminal arrival altitude
TACAN	UHF tactical air navigation aid
TAF	Aerodrome forecast
TA/H	Turn at an altitude/height
TAIL	Tail wind
TAR	Terminal area surveillance radar
TAS	True airspeed
TAX	Taxiing or taxi
TC	Tropical cyclone
TCAC	Tropical cyclone advisory centre
TCAS RA	Traffic alert and collision avoidance system resolution advisory
TCH	Threshold crossing height
*TCN	Terminal change notice
TCU	Towering cumulus
TDO	Tornado
TDZ	Touchdown zone
TECR	Technical reason
TEL	Telephone
TEMPO	Temporary or temporarily
TF	Track to fix
TFC	Traffic
TGL	Touch-and-go landing
*TGL	Temporary Guidance Leaflet
TGS	Taxiing guidance system
THR	Threshold
THRU	Through
THU	Thursday
TIBA	Traffic information broadcast by aircraft
TIL	Until
TIP	Until past . . . (place)
TKOF	Take-off
TL	Till (followed by time by which weather change is forecast to end)
TLOF	Touchdown and lift-off area
TMA	Terminal control area
*TMZ	Transponder mandatory zone
TN	Indicator for minimum temperature (used in the TAF code form)
TNA	Turn altitude
*TNC	Terminal navigation charge
TNH	Turn height
TO	To . . . (place)
*TOBT	Target off block time
TOC	Top of climb
TODA	Take-off distance available
TODAH	Take-off distance available, helicopter
TOP	Cloud top
TORA	Take-off run available
TOX	Toxic
TP	Turning point
TR	Track
TRA	Temporary reserved airspace
TRANS	Transmits or transmitter
TREND	Trend forecast
TRG	Training
TRL	Transition level
TROP	Tropopause
TS	Thunderstorm (in aerodrome reports and forecasts, TS used alone means thunder heard but no precipitation at the aerodrome)
TS	Thunderstorm (followed by RA = rain, SN = snow, PL = ice pellets, GR = hail, GS = small hail and/or snow pellets or combinations thereof, e.g. TSRASN = thunderstorm with rain and snow)
*TSA	Temporary segregated area

*TSAT	Target start-up approval time
TSUNAMI	Tsunami (used in aerodrome warnings)
TT	Teletypewriter
*TTOT	Target take-off time
TUE	Tuesday
TURB	Turbulence
T-VASIS	T visual approach slope indicator system
TVOR	Terminal VOR
TWR	Aerodrome control tower or aerodrome control
TWY	Taxiway
TX...	Maximum temperature (followed by figures in TAF)
TXL	Taxilane
TXT	Text [when the abbreviation is used to request a repetition, the question mark (IMI) precedes the abbreviation, e.g. IMI TXT] (to be used in AFS as a procedure signal)
TYP	Type of aircraft
TYPH	Typhoon

U

U	Upward (tendency in RVR during previous 10 minutes)
UA	Unmanned aircraft
UAB	Until advised by . . .
UAC	Upper area control centre
UAR	Upper air route
UAS	Unmanned aircraft system
*UAT	Universal access receiver
UDF	Ultra high frequency direction-finding station
UFN	Until further notice
UHDT	Unable higher due traffic
UHF	Ultra high frequency (300 to 3000 MHz)
UIC	Upper information centre
UIR	Upper flight information region
ULM	Ultra light motorized aircraft
ULR	Ultra long range
UNA	Unable
UNAP	Unable to approve
UNL	Unlimited
UNREL	Unreliable
UP	Unidentified precipitation (used in automated METAR/SPECI)
*UPS	Uninterrupted power supply
U/S	Unserviceable
*USAF	United States Air Force
UTA	Upper control area
UTC	Coordinated Universal Time
*UUP	Updated Airspace Use Plan
*UWT	Upper winds and temperature

V

V	Indicator for variations from the mean wind direction (used in the METAR/SPECI code forms)
VA	Heading to an altitude
VA	Volcanic ash
VAAC	Volcanic ash advisory centre
VAC	Visual approach chart (followed by name/title)
VAL	In valleys
VAN	Runway control van
VAR	Magnetic variation
VAR	Visual-aural radio range
VASIS	Visual approach slope indicator system
*VAT	Value-added tax
VC	Vicinity of the aerodrome (followed by FG = fog, FC = funnel clouds, SH = showers, PO = dust/sand whirls, BLDU = blowing dust, BLSA = blowing sand or BLSN = blowing snow, e.g. VC FG = vicinity fog)
VCY	Vicinity
VDF	Very high frequency direction-finding station
*VDL	Very high frequency data link
*VDP	Visual descent point

VER	Vertical	XS	Atmospherics
VFR	Visual flight rules		
VHF	Very high frequency (30 to 300 MHZ)		
VI	Heading to an intercept		Y
VIP	Very important person		
VIS	Visibility	Y	Yellow
*VLA	Very light aircraft	YCZ	Yellow caution zone (runway lighting)
VLF	Very low frequency (3 to 30 KHZ)	YES	Yes (affirmative; to be used in AFS as a procedure signal)
*VLOS	Visual line of sight		
VLR	Very long range	YR	Your
VM	Heading to a manual termination		
VMC	Visual meteorological conditions		
VNAV	Vertical navigation		Z
VOL	Volume (followed by I, II...)		
VOLMET	Meteorological information for aircraft in flight	Z	Coordinated Universal Time (in meteorological messages)
VOR	VHF omnidirectional radio range		
VORTAC	VOR and TACAN combination		
VOT	VOR airborne equipment test facility		
VPA	Vertical path angle		
VPT	Visual manoeuvre with prescribed track		
VRB	Variable		
VSA	By visual reference to the ground		
VSP	Vertical speed		
*VSS	Visual segment surface		
VTF	Vector to final		
VTOL	Vertical take-off and landing		
VV	Vertical visibility (used in the METAR/SPECI and TAF code forms)		

W

W	West or western longitude
W	White
W	Indicator for sea-surface temperature (used in the METAR/SPECI code forms)
WAAS	Wide area augmentation system
WAC	World Aeronautical Chart - ICAO 1:1 000 000 (followed by name/title)
WAFC	World area forecast centre
WB	Westbound
WBAR	Wing bar lights
WDI	Wind direction indicator
WDSPR	Widespread
WED	Wednesday
WEF	With effect from or effective from
WGS-84	World Geodetic System - 1984
WI	Within
WID	Width or wide
WIE	With immediate effect or effective immediately
WILCO	Will comply
WIND	Wind
WIP	Work in progress
WKN	Weaken or weakening
WNW	West-north-west
WO	Without
*WPR	Way-point reporting
WPT	Way-point
WRNG	Warning
WS	Wind shear
WSPD	Wind speed
WSW	West-south-west
WT	Weight
*WTC	Wake turbulence category
WTSPT	Waterspout
WWW	Worldwide web
WX	Weather
WXR	Weather radar

X

X	Cross
XBAR	Crossbar (of approach lighting system)
XNG	Crossing

THIS PAGE INTENTIONALLY LEFT BLANK